

# Technical Specifications

## Model: Triton Automatic Dosing System

### Notice

<b>Space</b>	0.3m x 0.7m x 0.8m (W, D, H) or more
<b>Electric</b>	Single phase, 220V, 3A
<b>Coolant</b>	Air pressure 3bar or more (Urethane hose (8mm or 10mm) connection)
<b>Remark</b>	N/A

### Triton, Automatic Dosing System

Triton is an automatic slurry supplier for suspension or lubricant using auto-head (Fobos-300). Triton has programmable function by touch screen and can supply the slurry evenly by spray type. Triton can also be control the supply and break time for whole operating time.

#### Features

- 6 holes / Individual slurry supplying at the same time (Maximum 4 holes)
- Supply and break time set-up
- Strong spray supply using air pressure
- Automatic start with polisher
- Free jet at the initial polishing

#### 1. Specification

- Size: 290mmW x 630mmD x 230mmH
- 220V, Single phase
- Regulator



- 5.6" Touch screen control panel
- Supply time set-up
- Break time set-up
- Whole operating time set-up
- Operation set-up
- Graphical display of operating and whole time
- Name set-up of supplying slurry
- Holder size: 80mm x 6holes

## 2. Service and Remark

- 1 year warranty
- Operation manual (1copy)
- Installation and education at the shipping place

