

characteristics ESD Stool 2 with castors

Article: 9468E artificial leather

Dimensions in mm

Seat:	H:	460-630
	B:	400
	T:	400



Packing data

Weight	kg	8,0
Volume	m ³	0,13

Base equipment

Benefit

Conductivity	The metal components have a conductive coating The high-comfort upholstery is also conductive Typical discharge resistance of 10 ⁶ Ohm Conductive castors.	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1. 100% ESD protection.
Seat	Extra large seat with a diameter of 400 mm.	Automatically encourages healthy posture and upright seating. The round front edge of the seat prevents blocked circulation in the thighs.
Finish for seat	ESD synthetic leather upholstery: High-level ESD synthetic leather Skai Tundra. Resistant to desinfectants, washable and easy-care Colour: black (2571).	The soft and comfortable upholstery provides a comfortable feel. However, damages caused by sharp parts can not be excluded. Ideal for the use in laboratory.
Seat	Stepless seat height setting from 460 - 630 mm supported by safety gas spring with protective cover.	Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt.
Functions / Mechanism	Ring release.	Height adjustment can be operated comfortable and easy in sitting position.
Base	Black 5 star base made from steel shape tube, conductive, powder-coated, black. Flat design.	Very high stability, longevity. Flat design prevents stumbling hazard.
Castors	Conductive Dual-wheel safety castors with load-sensitive brakes, for hard floors as standard.	Chairs are braked when not used which decreases the accident risk.
Materials	The materials used are recyclable.	Environmentally friendly.
Standards	DIN EN European standard 61340-5-1 for ESD-protected areas DIN 68 877 German GS "safety tested" mark of confirmity Quality Management System DIN EN ISO 9001 Regulation EWG Nr. 1836/93 Environmental Management System DIN ISO 14001.	100% ESD protection. Procuring is insured.
Warranty	10 year long term warranty, 3 years full warranty.	Guaranteed quality and high efficiency.