



## Semi-rigid Light Guide

# GLS2

MADE  
IN  
GERMANY

- High flexibility and luminous efficiency
- Best transmission
- Spot illumination
- Low head generation on object
- For halogen and LED cold light sources
- Versions with several flexible arms
- Adaptable to cold light sources from all manufacturers
- Adaptable to customer needs



## Technical Data

Diameter active light guide	4,5 mm
Light guide access	15 mm (Standard)
Beam angle	70°
Illumination	point-like
Number of arms	2
Diameter light output	13 mm
Diameter light input	44 mm
Outer tube diameter	10 mm
Temperature input (light source)	max. 230°C
Material tube	steel / brass, black paintet

## Versions

100-005914	GLS2-400-3.2	2-armed, arm length 400 mm, active diameter 3,2 mm
100-002929	GLS2-450-4.5	2-armed, arm length 450 mm, active diameter 4,5 mm
100-003875	GLS2-600-4.5	2-armed, arm length 600 mm, active diameter 4,5 mm
100-010596	GLS2-800-4.5	2-armed, arm length 800 mm, active diameter 4,5 mm
100-010597	GLS2-600+800-4.5	2-armed, arm length 600 mm + 800 mm, active diameter 4,5 mm

## Accessories

100-002917	Focusing optic	for active diameters 4,5 mm, f 30 mm
------------	----------------	--------------------------------------