



Incident Lamp

IL11

MADE
IN
GERMANY

- Flexible illumination thanks to semi-rigid arms
- Perfect incident light for microscopes
- Small dimensions of the lamp heads
- Flicker-free lighting for photographs and video
- Very high color rendering index (CRI)
- Brightness adjustable from 0 to 100%
- Very good price-performance ratio



Technical Data

Illuminance	400 klx (distance 2 cm)
Illuminant	2 × High CRI LED
Color temperature	5.600 K (natural white)
Color rendering index (CRI)	≥ 95
Brightness control	sensitive adjusting 0 - 100% with memory function
Power consumption	approx. 10 W
Input power supply	100 - 240 V AC, 50/60 Hz
Output power supply	24 V DC, 1 A
Protection class	III
Number of arms	2
Diameter for fixing rod	12 mm
Length power cord	1,40 m
Material	anodized aluminium
Color	black
Weight	approx. 0,6 kg
Dimensions control unit (l × w × h)	80 mm × 40 mm × 37 mm

Versions

100-012043	IL11-450 2-arm NW	2-armed, arm length 450 mm, natural white (5.600 K)
100-012094	IL11-600 2-arm NW	2-armed, arm length 600 mm, natural white (5.600 K)

Accessories

100-011893	X-Base	with fixing rod, 100 mm
100-011341	Stand Plate	with fixing rod, 100 mm
100-004760	Stand Plate	with fixing rod, 200 mm
100-004761	Stand Plate	with fixing rod, 400 mm
100-004778	Fixing for Microscope Stack	for incident lamps, diameter 25 mm
100-005120	Fixing for Microscope Stack	for incident lamps, diameter 32 mm
100-011656	IL Stand Adapter	for Nikon C-PSC